

TECHNICAL SPECIFICATIONS

Model	LHD model										
	Body type	Single cab				Double cab					
	Drive system	2WD		4WD	2WD		2WD Hi-Rider		4WD		
	Engine	2.4 MPI	2.5 TC DI-D	2.5 IC/TC DI-D	2.5 TC DI-D	2.4 MPI	2.5 TC DI-D	2.5 IC/TC DI-D	2.5 IC/TC DI-D High power	2.4 MPI	2.5 TC DI-D
	Price class	GL			GL	GL		GLX		GL	
	Model code	KJ4TENJMLW	KJ3TENJTL	KJ3TENJFL	KL3TENJTL	KJ4TJNJMLW	KJ3TJNJTL	KK3TJNUFL	KK3TJYUFL	KL4TJNJML	KL3TJNJTL
Dimensions and weights											
Overall length	mm	5075				5200				5200	
Overall width	mm	1785				1785				1785	
Overall height	mm	1655		1780	1655		1775		1775		
Wheelbase	mm	3000				3000				3000	
Ground clearance	mm	200		200 (212*1)	200		200 (212*1)		200 (212*1)		
Cargo floor height	mm	710		845	715		845		845		
Curb weight	kg	1410	1500	1505	1690	1510	1590	1705	1735	1690	1775
Gross vehicle weight	kg	2570			2760	2525	2570	2760		2760	2850
Seating capacity	persons	3				6		5		6	
Performance											
Max. speed*	km/h	169	152	165	147	169	152	167	169	161	147
Min. turning radius	m	5.7			5.9	5.7		5.9		5.9	
Engine											
Type (code)		2.4-liter 16-valve inline-4 SOHC (4G64)	2.5 liter 16-valve inline-4 turbocharged DOHC diesel (4D56)	2.5 liter 16-valve inline-4 intercooled turbocharged DOHC diesel (4D56)	2.5 liter 16-valve inline-4 turbocharged DOHC diesel (4D56)	2.4-liter 16-valve inline-4 SOHC (4G64)	2.5 liter 16-valve inline-4 turbocharged DOHC diesel (4D56)	2.5 liter 16-valve inline-4 intercooled turbocharged DOHC diesel Standard (4D56)	2.5 liter 16-valve inline-4 intercooled turbocharged DOHC diesel High Power (4D56)	2.4-liter 16-valve inline-4 SOHC (4G64)	2.5-liter 16-valve inline-4 turbocharged DOHC diesel (4D56)
Displacement	cc	2,351	2,477			2,351	2,477			2,351	2,477
Max. output (EEC net)	kW (PS)/rpm	97 (132)/5,250	81 (110)/4,000	94 (128)/4,000	81 (110)/4,000	97 (132)/5,250	81 (110)/4,000	100 (136)/4,000	131 (178)/4,000	97 (132)/5,250	81 (110)/4,000
Max. torque (EEC net)	N·m (kg-m)/rpm	202 (20.6)/4,000	200 (20.4)/1,500-3,500	240 (24.5)/1,500-3,500	200 (20.4)/1,500-3,500	202 (20.6)/4,000	200 (20.4)/1,500-3,500	324 (33.1)/2,000	400 (40.8)/2,000	202 (20.6)/4,000	200 (20.4)/1,500-3,500
Fuel System											
Fuel supply system		ECI-MULTI (Electronic Controlled Injection-Multi Point Injection)	Electronic Common Rail direct injection			ECI-MULTI (Electronic Controlled Injection-Multi Point Injection)	Electronic Common Rail direct injection			ECI-MULTI (Electronic Controlled Injection-Multi Point Injection)	Electronic Common Rail direct injection
Fuel tank capacity	liters	75				75				75	
Drive system											
Type		2WD		Easy Select 4WD	2WD				Easy Select 4WD		
Transmission											
Type		5-speed manual			5-speed manual				5-speed automatic with Sports Mode	5-speed manual	
Steering											
Type		Rack-and-pinion, power assisted									
Suspensions											
Front		Wishbone, coil springs									
Rear		Elliptic leaf, springs									
Brakes											
Front		Ventilated disc brakes (Diameter 270mm)			Ventilated disc Brakes (Diameter 294mm)	Ventilated disc brakes (Diameter 270mm)		Ventilated disc brakes (Diameter 294mm)			
Rear		11.6-inch drum brakes				10-inch drum brakes		11.6-inch drum brakes			
Tires and wheels											
Tires (front and rear)	Standard	195R15C 8PR			205R16C 8PR	195R15C 8PR		205R16C 8PR			

TECHNICAL SPECIFICATIONS

Model	LHD model								RHD model										
	Body type	Double cab						Single cab		Double cab									
	Drive system	4WD						2WD	4WD	2WD	4WD								
	Engine	2.5 IC/TC DI-D	2.5 IC/TC DI-D		2.5 IC/TC DI-D High power		2.4 IC/TC DI-D High power		2.5 TC DI-D	2.5 TC DI-D	2.5 TC DI-D	2.5 TC DI-D	2.5 IC/TC DI-D		2.5 IC/TC DI-D High power		2.4 IC/TC DI-D High power		
	Price class	GLX	GLS						GL		GL	GL	GLS						
Model code	KL3TJNUFL	KL3TJNHFL	KL3TJYHFL	KL3TJNHFPFL	KL3TJYHFPL	KL1TJJHFPL	KL1TJYHFPL	KJ3TENJTR	KL3TENJTR	KJ3TJNJTR	KL3TJNJTR	KL3TJNHFR	KL3TJYHFR	KL3TJNHFR	KL3TJYHFR	KL1TJJHFPR	KL1TJYHFPR		
Dimensions and weights																			
Overall length	mm	5200						5075		5200									
Overall width	mm	1785	1815		1815		1785		1785		1785		1815		1815		1815		
Overall height	mm	1775	1780		1780		1655		1780	1655		1775	1780		1780		1780		
Wheelbase	mm	3000						3000		3000									
Ground clearance	mm	200 (207*1)	205 (205*1/220*2/205*3/220*4)		205 (205*1)		200	200 (212*1)	200	200 (212*1)	205 (205*1/220*2/205*3/220*4)	205 (205*1/220*2/205*3/220*4)		205 (205*1/220*2/205*3/220*4)		205 (205*1/220*2/205*3/220*4)			
Cargo floor height	mm	845	850		850		710	845	715	845	850		850		850		850		
Curb weight	kg	1805	1820	1830	1835	1850	1840	1845	1500	1690	1590	1775	1820	1830	1835	1850	1835	1840	
Gross vehicle weight	kg	2850		2870	2900	2870		2570	2760	2570	2850	2850		2870	2900	2870			
Seating capacity	persons	5						3		5		6							
Performance																			
Max. speed*	km/h	167	165	179	175	179	177	152	147	152	147	167	165	179	175	179	177		
Min. turning radius	m	5.9						5.7	5.9	5.7	5.9	5.9							
Engine																			
Type (code)		2.5-liter 16-valve inline-4 intercooled turbocharged DOHC diesel Standard (4D56)			2.5-liter 16-valve inline-4 intercooled turbocharged DOHC diesel High Power (4D56)		2.4-liter 16-valve inline-4 intercooled turbocharged DOHC diesel High Power (4N15)		2.5 liter 16-valve inline-4 turbocharged DOHC diesel (4D56)		2.5 liter 16-valve inline-4 turbocharged DOHC diesel (4D56)	2.5-liter 16-valve inline-4 turbocharged DOHC diesel (4D56)	2.5-liter 16-valve inline-4 intercooled turbocharged DOHC diesel Standard (4D56)		2.5-liter 16-valve inline-4 intercooled turbocharged DOHC diesel High Power (4D56)		2.4-liter 16-valve inline-4 intercooled turbocharged DOHC diesel High Power (4N15)		
Displacement	cc	2,477						2,442		2,477		2,477	2,477	2,477		2,477		2,442	
Max. output (EEC net)	kW (PS)/rpm	100 (136)/4,000	100 (136)/4,000		131 (178)/4,000		133 (181)/3,500		81 (110)/4,000	81 (110)/4,000	81 (110)/4,000	81 (110)/4,000	100 (136)/4,000		131 (178)/4,000		133 (181)/3,500		
Max. torque (EEC net)	N·m (kg·m)/rpm	324 (33.1)/2,000	324 (33.1)/2,000		400 (40.8)/2,000		430 (43.9)/2,500		200 (20.4)/1,500-3500	200 (20.4)/1,500-3500	200 (20.4)/1,500-3500	200 (20.4)/1,500-3500	324 (33.1)/2,000		400 (40.8)/2,000		430 (43.9)/2,500		
Fuel System																			
Fuel supply system		Electronic Common Rail direct injection						Electronic Common Rail direct injection		Electronic Common Rail direct injection									
Fuel tank capacity	liters	75						75		75									
Drive system																			
Type		Easy Select 4WD		Easy Select 4WD	Super Select 4WD-II	Easy Select 4WD	Super Select 4WD-II	2WD	Easy Select 4WD	2WD	Easy Select 4WD		Super Select 4WD-II	Easy Select 4WD	Super Select 4WD-II				
Transmission																			
Type		5-speed manual	5-speed automatic with Sports Mode	5-speed manual	5-speed automatic with Sports Mode	6-speed manual	5-speed automatic with Sports Mode	5-speed manual		5-speed manual		5-speed automatic with Sports Mode	5-speed manual	5-speed automatic with Sports Mode	6-speed manual	5-speed automatic with Sports Mode			
Steering																			
Type		Rack-and-pinion, power assisted						Rack-and-pinion, power assisted											
Suspensions																			
Front		Wishbone, coil springs						Wishbone, coil springs											
Rear		Elliptic leaf, springs						Elliptic leaf, springs											
Brakes																			
Front		Ventilated disc Brakes (Diameter 294mm)						Ventilated disc brakes (Diameter 270mm)	Ventilated disc Brakes (Diameter 294mm)	Ventilated disc brakes (Diameter 270mm)	Ventilated disc Brakes (Diameter 294mm)								
Rear		11.6-inch drum brakes						10-inch drum brakes	11.6-inch drum brakes	10-inch drum brakes	11.6-inch drum brakes								
Tires and wheels																			
Tires (front and rear)	Standard	205R16C 8PR	245/70R16		245/70R16		195R15C 8PR	205R16C 8PR	195R15C 8PR	205R16C 8PR	245/70R16								

*1 Model with reinforced front skid plate and floor undercover

*2 Model with reinforced front skid plate and floor undercover + 265/70R16 tires

*3 Model with reinforced front skid plate and floor undercover + 245/65R17 tires

*4 Model with floor undercover + 265/70R16 tires

* Measured by MITSUBISHI MOTORS CORPORATION

Note: These specifications are subject to change without notice. Please consult your local Mitsubishi Motors dealer/distributor for detailed specifications.

Note: Equipment may vary by market. Please consult your local Mitsubishi Motors dealer/distributor for details.